

Universal cutting saw
EST 350.2



Ø 350

SPECIFICATIONS	EST 350.2
Power input	2400 W
Rated voltage	230 V ~
No-load speed	3900 rpm
Max. disc diameter	350 mm
Max. cutting depth	120 mm
Max. cutting length	250 mm
Spindle connection	Ø 25.4 mm
Weight	19 kg
Order no.	06637000
Supplied	in a box incl. diamond cutting disc Ø 350 mm and assembly tools

The precise and dust free machine for dry cutting

APPLICATION:

- Cutting of stone materials, e.g. concrete, natural stone, bricks
- Ideal for precise cuts on pavements work
- cutting of steel, plastic and similar materials with new universal cutting blade (accessory)
- Gardening and landscaping, road and pavement construction, for clinker-cutting etc.

FEATURES:

- New ergonomic handle - comfortable operation from all working positions
- Cutting table made of cast aluminum - robust and durable
- Optimized dust collection due to closed base at the machine table
- Tool-less adjustable quick clamping device – safe fixing to the work area
- Spindle lock – easy tool change
- Transportation lock in hinged position – handy and safe transport of the machine
- Angular stop stepless adjustable 0-45° – easy and precise mitre cuts
- Starting current limiter
- Nozzle diameter 35 mm – direct connection of industrial vacuum cleaner of EIBENSTOCK DSS series


Cutting table (cutting capacity at 90° cuts)

Cutting depth: 80 mm 100 mm 120 mm

Cutting length: 250 mm 200 mm 150 mm



adjustable angle stop



quick clamping device

